

120 AGB series

120X120X38mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
- Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 450g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
- 葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 450克



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油承軸/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow		Max. Static Pressure		Sound	Weight
機型	軸承	電壓	操作電壓	電流	轉速	最大風量		最大風壓		噪音	重量
P/N	B/S/F	V	V	A	RPM	m³/min	CFM	mm-H ₂ O	In-H ₂ O	dB(A)	g
AGB12038*12L	B	12	6.0~13.2	1.63	4000	4.98	175.93	18.74	0.74	55.42	450
AGB12038*12M	B	12	6.0~13.2	2.30	4800	6.03	213.06	26.95	1.06	60.25	450
AGB12038*12H	B	12	6.0~13.2	4.50	5500	6.89	243.33	34.98	1.38	64.35	450
AGB12038*24L	B	24	12.0~26.4	0.71	4000	4.98	175.93	18.74	0.74	55.42	450
AGB12038*24M	B	24	12.0~26.4	1.12	4800	6.03	213.06	26.95	1.06	60.25	450
AGB12038*24H	B	24	12.0~26.4	1.71	5500	6.89	243.33	34.98	1.38	64.35	450
AGB12038*24U	B	24	12.0~26.4	2.48	6200	8.27	292.19	43.71	1.72	66.88	450
AGB12038*48L	B	48	24.0~52.8	0.55	4000	4.98	175.93	18.74	0.74	55.42	450
AGB12038*48M	B	48	24.0~52.8	0.69	4800	6.03	213.06	26.95	1.06	60.25	450
AGB12038*48H	B	48	24.0~52.8	0.89	5500	6.89	243.33	34.98	1.38	64.35	450
AGB12038*48U	B	48	24.0~52.8	1.20	6200	8.27	292.19	43.71	1.72	66.88	450

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

